


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : C10L 1/18, C10G 75/02, C10L 10/04, E21B 41/02, C07C 69/593</p>	<p>A1</p>	<p>(11) International Publication Number: <b>WO 97/45507</b>  (43) International Publication Date: 4 December 1997 (04.12.97)</p>
<p>(21) International Application Number: PCT/GB97/01469 (22) International Filing Date: 30 May 1997 (30.05.97)  (30) Priority Data: 9611406.1 31 May 1996 (31.05.96) GB 9619701.7 20 September 1996 (20.09.96) GB  (71) Applicant (for all designated States except US): THE ASSOCIATED OCTEL COMPANY LIMITED [GB/GB]; 23 Berkeley Square, London W1X 6DT (GB).  (72) Inventors; and (75) Inventors/Applicants (for US only): MACMILLAN, John, Alexander [GB/GB]; The Associated Octel Co., Ltd., Oil Sites Road, Ellesmere Port, South Wirral L65 4HF (GB). BREWER, Mark, Lawrence [GB/GB]; The Associated Octel Co., Ltd., Oil Sites Road, Ellesmere Port, South Wirral L65 4HF (GB).  (74) Agents: MATTHEWS, Derek, Peter et al.; Frank B. Dehn &amp; Co., 179 Queen Victoria Street, London EC4V 4EL (GB).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  Published With international search report.</p>	
<p>(54) Title: FUEL ADDITIVES</p> <p>(57) Abstract</p> <p>Compounds of formula (I) where R<sub>1</sub> is a C<sub>10</sub>-C<sub>32</sub> alkenyl group and R<sub>2</sub> and R<sub>3</sub> are (-OCH<sub>2</sub>CH<sub>2</sub>)<sub>n</sub>OH, (-OCH<sub>2</sub>CHCH<sub>3</sub>)<sub>n</sub>OH or -OCH<sub>2</sub>CHOHCH<sub>2</sub>OH in which n is an integer from 1 to 10 are lubricity and corrosion-prevention additives for fuels.</p> <div style="text-align: right;">  <p>(I)</p> </div>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

### Fuel additives

This invention relates to fuel additives, more particularly to additives which increase the lubricity of the fuel and avoid undesirable interactions with the other additives now commonly present in fuels. The additives have also been found to possess surprisingly useful anti-corrosion properties.

It is known to add a minor proportion of a long chain fatty acid to liquid hydrocarbon fuels to increase the lubricity of the fuel, that is the ability to prevent wear on contacting metal surfaces. Increased lubricity results in lower wear to the surface, as measured for example by the well known wear scar test described in more detail hereinafter. Fatty acids which have been used for this purpose include di-linoleic acid. However, the increasing number of additives now present in fuels, and increased dosing levels, means that a need is arising for lubricity additives with an inherently lower tendency to interact with other fuel and lubricant additives. Improved lubricity performance for such compounds, relative to known lubricity additives, would also be desirable.

Esters of fatty acids have also been proposed as lubricity additives. Whilst the acid functions of these molecules are blocked by an alkyl ester group and so are not available for interaction with other fuel additives, it is important that the performance of the lubricity additive is not reduced by esterification, so that a delicate balance of properties is required.

US-A-4448586 (to Weidig) discloses liquid fuels having anti-corrosion properties for use in internal

- 2 -

combustion engines. The corrosion inhibition is discussed in relation to alkanol-type fuels and the reactant ratios are such that  $\text{RCOO} \cdot \text{CH}_2\text{CH}_2 \cdot \text{OOCR}$  structures are present.

US-A-4874395 (to Meyer) also discloses corrosion inhibitor compositions for hydrocarbon fuels comprising a  $\text{C}_{10}\text{-C}_{24}$  alkenyl succinimide anhydride partially esterified with a water-soluble glycol. However, the ester is then neutralised with an amine in order to neutralise residual acid groups. Such acid groups are not present in the compounds of the present invention.

FR-A-2169718 (to Institut Français du Pétrole, des Carburants et Lubrifiants) discloses lubricating oils comprising 10 to 100% of esters, polyesters or esters of ethers of polyalkyleneglycols represented by the formula  $\text{HO}(\text{R-O})_n\text{H}$  wherein each R is a divalent aliphatic  $\text{C}_2\text{-C}_5$  radical and  $n = 2\text{-}50$ .


GB-A-1055337 (to Lubrizol) discloses oil-soluble esters of a substantially hydrocarbon-substituted succinic acid wherein the substantially saturated hydrocarbon substituent has at least 50 aliphatic carbon atoms.

GB-A-1306233 (to Lubrizol) discloses a fuel composition comprising a major amount of a petroleum and a minor amount of a dispersant composition comprising at least one oil-soluble carboxylic dispersant including a substantially saturated hydrocarbon-substituted carboxylic group having at least 30 aliphatic carbon atoms in the hydrocarbon substituent and a stock petroleum fraction, the weight ratio of petroleum fraction to carboxylic dispersant being from 20:1 to 1:10.

- 3 -

We have now discovered a class of esterified alkenyl succinic acids which, while demonstrating excellent performance as lubricity additives, also offer improved compatibilities with other fuel and lubricant additives.

The novel compounds are represented by the general formula (I)



where  $R_1$  is a  $C_{10}$ - $C_{32}$  alkenyl group, such as an olefin or polyolefin,  $R_2$  and  $R_3$  are  $\{OCH_2CH_2\}_nOH$ ,  $\{OCH_2CHCH_3\}_nOH$  or  $-OCH_2CHOHCH_2OH$  with  $n = 1-10$ .

$R_1$  is most preferably a  $C_{12}$ - $C_{26}$  group. The value of  $n$  is preferably 1 or 2.

The compounds of formula (I) may be added to middle distillate fuels of poor lubricity, such as those with poor inherent lubricity, and those which have been exposed to hydrotreatment or desulphurisation processes thereby lowering the sulphur concentration to 0.5% w/w or less, for example diesel fuels (typical distillation range 150-400°C) and heating oils (typical distillation range 150-450°C), and also to gasolines (typical distillation range 30-210°C), kerosines (typical distillation range 140-300°C) and heavy fuel oils (typical distillation range 300-600°C). A further aspect of the invention thus comprises methods of increasing the lubricity of such fuels by addition of the compounds of the invention.

- 4 -

Compounds of formula (I) may be dosed in amounts between 5 and 5000 ppm, preferably between 10 and 500 ppm and most preferably between 30 and 300 ppm, to improve the lubricity properties of the fuels.

Diesel fuels and heating oils will typically contain less than 0.2% w/w sulphur and may contain, in addition to the additive compositions of this invention, any of the other additives commonly added as minor components, such as cetane improvers, cold flow improvers, detergent/dispersant additives, antifoam additives, dehazing additives, combustion improvers, antioxidants, etc.

As used herein, "gasoline" refers to motor fuels meeting ASTM standard D-439, and includes blends of distillate hydrocarbon fuels with oxygenated components, such as MTBE, ETBE, ethanol, etc. as well as the distillate fuels themselves. The fuels may be leaded or unleaded, and may contain, in addition to the additive compositions of this invention, any of the other additives conventionally added to gasolines, such as scavengers, anti-icing additives, octane requirement improvers, detergent packages, antioxidants, demulsifiers, corrosion inhibitors, etc.


The compounds of formula (I) have also been found to possess surprisingly useful anti-corrosion properties. Thus in certain oil refinery and pipeline cargo applications a corrosion inhibitor is required which will be resistant to base neutralisation. The base, typically sodium hydroxide, can be present in fuels which have undergone a refinery sweetening treatment. The consequence of base neutralisation is deactivation of added corrosion inhibitors and consequent levels of rust which are typical of a fuel without added corrosion inhibitors.

The compounds of formula (I), however, have been found to provide effective corrosion inhibition which is resistant to base deactivation. Thus a further aspect of the invention provides a method of inhibiting corrosion on a metal surface exposed to a liquid hydrocarbon fuel, comprising the addition to said fuel of a compound of formula (I) as defined above. The metal surface, typically a pipeline or other metal vessel as used in fuel transport and/or in known refinery processes, will generally be of iron or steel.

Compounds of formula I may be added in amounts between 5 and 5000 ppm, preferably between 10 and 500 ppm and most preferably between 30 and 300 ppm, to achieve the desired corrosion inhibition in the fuel.

The invention also provides fuel additive compositions suitable for use in any of the previous aspects of the invention, the compositions comprising one or more compounds of formula (I) in a fuel-miscible solvent, for example toluene, xylene or Shellsol (available from Shell), and optionally other ingredients conventionally used in fuel additive packages.

The compounds of formula (I) may for example be prepared by reacting an anhydride of formula



with an alcohol of formula R<sub>2</sub>OH and/or R<sub>3</sub>OH where R<sub>2</sub> and R<sub>3</sub> are as defined above. The anhydride is conveniently prepared by addition of the olefin or polyolefin across the double bond of maleic anhydride by processes known per se.

- 6 -

The invention is illustrated by the following examples.

Preparation of compounds.

- A. A reaction mixture containing 59g of maleic anhydride together with 190g of a polyisobutylene, such as NAPVIS XD 35 (available from BP), was heated at 230°C for 16 hours. After this period the solution was vacuum distilled for 4 hours and then cooled to room temperature. 170g of toluene and 81g of diethylene glycol were then added and the mixture was heated at 140°C for 8 hours with reaction product water continuously removed. The reaction mixture was cooled to room temperature and the viscous liquid remaining in the reactor was used directly as fuel additive.
- B. 50g of maleic anhydride was added over 3 hours to 200g of a polyisobutylene, such as INDOPOL L14 (available from Amoco), which was heated to 200°C. The reaction mixture was then heated at 200°C for a further 16 hours. After this period the reaction mixture was vacuum distilled for 2 hours and then cooled to room temperature. 186g of ethylene glycol was then added to the reaction mixture and the mixture was heated at 170° for 12 hours. After this period the reaction mixture was vacuum distilled for 2 hours and then cooled to room temperature. The viscous liquid remaining in the reactor was used directly as fuel additive.
- C. A reaction mixture containing 18g of ethylene glycol together with 35g of 2-dodecen-1-ylsuccinic anhydride and 36g of toluene was heated to 160°C with Dean Stark water removal until the reaction was completed. The viscous liquid remaining in the



- 7 -

reactor was used directly as fuel additive.

- D. 358g of polyisobutenylsuccinic anhydride, prepared from maleic anhydride and NAPVIS X10 (available from BP) in the same manner as (B) above, was mixed with 372g of ethylene glycol and the mixture was heated at 170-190°C for 12 hours with continuous removal of by-product water. After this period the reaction mixture was vacuum distilled for 2 hours then cooled to room temperature. The viscous liquid can be used directly as a fuel additive or can be diluted with SHELLSOL AB (available from Shell).

- 8 -

Improvement of Fuel Lubricity

A High Frequency Reciprocating Rig (HFRR) bench test, such as described in SAE Technical Paper 932692, can measure the lubricity of base fuels and fuels dosed with lubricity additives. The results of such a test are reported as ball wear in terms of mean wear scar diameter. Lower wear scar diameters are indicative of better lubricity. HFRR wear scar diameter results (in  $\mu\text{m}$ ) are compared below for typical North European middle distillate fuels which have been treated with compounds of formula (I), a commercial fatty acid based additive, and an alkyl ester of a commercial fatty acid (ethyl linoleate) respectively. The fuels contain less than 0.05% w/w sulphur content.

	Base Fuel	100 ppm	200 ppm
Commercial Fatty Acid			
Based Additive	525	471	434
Ethyl Linoleate	513	590	578
Compound B	525	420	380
Compound C	525	454	426

	Base Fuel	50 ppm	100 ppm
Compound A	660	555	552

- 9 -

Interaction Tests

Precipitation tests can be employed as an indication of the severity of the interactions between lubricity additive and lubricants, a typical test is described in SAE Technical Paper 872119. Interaction test results are presented below for compound B and a commercial fatty acid additive.

	DAY							
	0	1	2	3	4	5	6	7
100 mg/L Commercial Fatty Acid Based Additive	-	-	-	1	*	*	2	2
300 mg/L Commercial Fatty Acid Based Additive	-	-	1	2	*	*	3	3
100 mg/L Compound B	-	-	-	-	*	*	-	-
300 mg/L Compound B	-	-	-	-	*	*	-	-

- |                     |                       |
|---------------------|-----------------------|
| - No Precipitate    | 4 Medium Precipitate  |
| 1 Minute Trace      | 5 Heavy Precipitate   |
| 2 Trace Precipitate | 5 Sticky Precipitate  |
| 3 Light Precipitate | * Not Rated (Weekend) |

- 10 -

Corrosion Inhibition in Fuels

A standardised corrosion test, such as the National Association of Corrosion Engineers (NACE) standard test TM-01-72, can measure the effectiveness of corrosion inhibitors which are introduced into pipeline cargoes to prevent rusting caused by traces of moisture condensing from the products. The results of such a test are reported as a relative rating on the scale A-E. Corrosion ratings and percentage rust are compared below for samples of iso-octane which has been treated with a compound of formula (I), a commercial fatty acid based additive and a commercial non-acid lubricity additive. Iso-octane is employed for this test as a standard fuel medium to eliminate fuel-dependent effects.

Conc Additive (mg/l)

<u>in iso-octane</u>	0	5.7	11.4	22.8
----------------------	---	-----	------	------

Commercial fatty acid based additive	E 90	A 0	-	-
---	------	-----	---	---

Compound B	E 90	B++ 0.5	A 0	A 0
------------	------	---------	-----	-----

Commercial non-acid lubricity additive	E 90	D 60	B 15	B 15
---	------	------	------	------

<u>Rating</u>	<u>Proportion of test surface rusted</u>
---------------	--

A	None
B++	Less than 0.1% (2 or 3 spots of no more than 1mm diameter)
B+	Less than 5%
B	5% to 25%
C	25% to 50%
D	50% to 75%
E	75% to 100%

- 11 -

Maintenance of corrosion inhibition in "caustic" fuels


The reduction in corrosion inhibitor effectiveness in fuels containing alkali is demonstrated by the inhibitor's resistance to caustic extraction. One such caustic extraction screening test involves dosing fuels with 5% v/v of 8% w/w NaOH(aq) and then 5% v/v H<sub>2</sub>O before corrosion testing via the NACE protocol.

Conc Additive (mg/l)

<u>in iso-octane</u>	<u>0</u>	<u>4.3</u>	<u>8.6</u>
Commercial fatty acid based additive	E 90	E 90	E 90
Compound B	E 90	B+ 2	B+ 2

Claims

1. A compound of formula (I):



where R<sub>1</sub> is a C<sub>10</sub>-C<sub>32</sub> alkenyl group and R<sub>2</sub> and R<sub>3</sub> are {OCH<sub>2</sub>CH<sub>2</sub>}<sub>n</sub>OH, {OCH<sub>2</sub>CHCH<sub>3</sub>}<sub>n</sub>OH or -OCH<sub>2</sub>CHOHCH<sub>2</sub>OH with in which n is an integer from 1 to 10.

2. A compound according to claim 1 wherein R<sub>1</sub> is a C<sub>12</sub>-C<sub>26</sub> alkenyl group.
3. A compound according to claim 1 wherein n is 1 or 2.
4. A fuel composition comprising a liquid hydrocarbon fuel and a compound of formula (I) according to claim 1.
5. A fuel according to claim 4 wherein the hydrocarbon fuel comprises a middle distillate fuel, gasoline, kerosine or heavy fuel oil.
6. A fuel according to claim 4 wherein said compound of formula (I) is present in a concentration of 5 to 5000 ppm by weight.
7. A fuel according to claim 6 wherein said compound is present in a concentration of 10 to 500 ppm by weight.
8. A fuel according to claim 7 wherein said compound is present in a concentration of 30 to 300 ppm by weight.

- 13 -

9. A method of increasing the lubricity of a liquid hydrocarbon fuel comprising the addition to said fuel of a compound of formula (I) as defined in any of claim 1.

10. A method of inhibiting corrosion on a metal surface exposed to a liquid hydrocarbon fuel, comprising the addition to said fuel of a compound of formula (I) according to claim 1.

11. An additive composition suitable for addition to a hydrocarbon fuel comprising a compound of formula (I) according to claim 1 in a fuel-miscible solvent.

# INTERNATIONAL SEARCH REPORT

Int. .onal Application No  
PCT/GB 97/01469

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C10L1/18 C10G75/02 C10L10/04 E21B41/02 C07C69/593

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C10L C10G E21B C07C C10M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 448 586 A (WEIDIG) 15 May 1984 cited in the application see column 7, line 56 - column 8, line 16 ---	1-11
A	US 4 874 395 A (MEYER) 17 October 1989 cited in the application see the whole document ---	1-11
X	FR 2 169 718 A (I.F.P.) 14 September 1973 cited in the application see page 6, line 6; claim 3 see page 4, line 14 ---	1,4,5,9, 11
A	GB 1 055 337 A (LUBRIZOL) 18 January 1967 cited in the application see page 1, line 11 - line 55 see page 4, line 8 see page 3, line 94 - line 95 ---	1-11
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

26 August 1997

Date of mailing of the international search report

08.09.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

De La Morinerie, B



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 97/01469

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 20 29 804 A (LUBRIZOL) 23 December 1970 cited in the application see page 13 ---	1-11
A	US 5 080 817 A (MEYER) 14 January 1992 see the whole document ---	1-11
A	EP 0 235 868 A (SHELL) 9 September 1987 see page 3, line 19 - line 22 ---	1-11
A	WO 94 17160 A (EXXON) 4 August 1994 see abstract ---	1-11
A	US 2 993 773 A (STROMBERG) 25 July 1961 see column 4, line 25 - line 30 see column 6 ---	1-11
A	GB 981 850 A (SHELL) 27 January 1965 see page 1, line 61 - line 67 ---	1,3,11
A	GB 896 376 A (MONSANTO) 16 May 1962 see abstract -----	1-11

# INTERNATIONAL SEARCH REPORT

Int. Application No.

PCT/GB 97/01469

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4448586 A	15-05-84	NONE	
US 4874395 A	17-10-89	NONE	
FR 2169718 A	14-09-73	FR 2187893 A	18-01-74
		US 3871837 A	18-03-75
		BE 799904 A	23-11-73
		BE 792960 A	19-06-73
		CA 996538 A	07-09-76
		DE 2263243 A	12-07-73
		DE 2327546 A	13-12-73
		GB 1425661 A	18-02-76
		GB 1417590 A	10-12-75
		JP 48074507 A	08-10-73
		NL 7300029 A	03-07-73
		NL 7307707 A	04-12-73
GB 1055337 A		DE 1271877 B	
		FR 1396645 A	02-08-65
		US 3381022 A	30-04-68
		US 3522179 A	28-07-70
		US 3542680 A	24-11-70
		US 3579450 A	18-05-71
		US 3632510 A	04-01-72
DE 2029804 A	23-12-70	BE 752050 A	16-12-70
		FR 2046806 A	12-03-71
		GB 1306233 A	07-02-73
US 5080817 A	14-01-92	NONE	
EP 235868 A	09-09-87	AU 589501 B	12-10-89
		AU 6973387 A	10-09-87
		BR 8701013 A	29-12-87
		CA 1309585 A	03-11-92
		JP 8032896 B	29-03-96
		JP 62218490 A	25-09-87
		US 4728340 A	01-03-88
WO 9417160 A	04-08-94	AT 148157 T	15-02-97

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 97/01469

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9417160 A		AU 676713 B AU 5969794 A BR 9405814 A DE 69401576 D DE 69401576 T EP 0608149 A EP 0680506 A ES 2098125 T FI 953499 A JP 8505893 T NO 952830 A ZA 9400447 A	20-03-97 15-08-94 05-12-95 06-03-97 28-05-97 27-07-94 08-11-95 16-04-97 20-09-95 25-06-96 08-09-95 01-09-94
US 2993773 A	25-07-61	NONE	
GB 981850 A		BE 638130 A DE 1250583 B FR 1370420 A NL 134315 C NL 283936 A US 3331776 A	14-12-64 18-07-67
GB 896376 A		US 3045042 A	17-07-62